

Our flagship model, the PTC520 is what we would describe as the next generation of tyre changer. The traditional 4 jaw clamping turntable is replaced with a centre post design ensuring the rim is held securely.

Our patented 'Lever/No Lever' technology means that the machine can be switched between leverless and conventional demount head, giving it class-leading versatility. An integral wheel lifter completes this luxury specification.

> The PTC520 moves away from the conventional turntable; instead it boasts a centre post capable of changing up to 30" wheels. This has been paired with a robust manual wheel lock for a secure hold whilst working on wheels of all sizes.

> > 3") "

PSI

## SPECIFICATIONS

Rim clamping range:	12"-30"
Max tyre diameter:	1100 mm (4
Max tyre width:	390 mm (19
Bead breaker cylinder force	
at 10 bar:	3800 N
Operating pressure:	10 bar/145
Motor power:	220 V
Rotating speed:	7 rpm
Pre-set tyre inflation pressure:	50 psi

## FEATURES

- Fully automatic tyre machine capable of changing up to 30" wheels
- Manual wheel lock
- Reinforced vertical arm and body
- Oversize bead breaker arm with double axis blade
- Ergonomic position of bead breaker pedal

- Inflation pedal with tool tray
- Pneumatic wheel lift
- Lever-less mounting head (Lever/No Lever)
- Pneumatically controlled rear tilting column (saving you set up time)
- Triple attachment assist arm enabling you to easily cope with run flat and low profile tyres
- 2 year parts and labour warranty